



Technical data

Voltage	U	230	V
Phase		1	~
Frequency		50	Hz
Speed		1400	RPM
Power consumption	P _e	450	W
Nominal current	I	1.9	A
Maximum current	I	2.1	A
Capacitor		12/400	μF
Ambient temperature	T _{amb min/max}	-25...40	°C
Insulation Class		CL.F	
IP Class Fan		IP55	
Sound pressure level at 2 m	L _p	66	dB(A)
Weight		8.7	kg
Packing dimensions		510x510x315	mm

Fan details


Impeller blades	6
Impeller type	3
Impeller system	C
Impeller material	PP

Control options

Triac controller	Yes
Transformer	Yes
Frequency drive	Yes
Intelligent Fan Drive	Yes

Characteristics

0 Pa 8400 m³/h
50 Pa 7250 m³/h



Please note: Picture may deviate from original product

Approval(s)




ErP 2015


No.

Wiring diagram - Fan

AA01 - 1 Phase - Standard - CCW



Dimensions



VOSTERMANS
VENTILATION

Vostermans Ventilation B.V.
Venlo - The Netherlands
+31 (0)77 389 32 32
ventilation@vostermans.com
www.vostermans.com

Vostermans Ventilation Inc.
Bloomington, IL - U.S.A.
+1 309 827 9798
ventilation@vostermansusa.com
www.vostermansusa.com

Vostermans Ventilation Ltd. Co.
Shanghai - China
+86 21 5290 2889/2899
ventilation@vostermanschina.com
www.vostermans.com

Vostermans Ventilation Sdn. Bhd.
Tmn Klang Jaya - Malaysia
+60 (0)33324 3638
ventilation@vostermansasia.com
www.vostermansasia.com